

Atty. Dkt. No. 037145-3101

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A method for data repair in a point-to-multipoint communications system, the method comprising:
 - transmitting data from a sender to a plurality of receivers via a point-to-multipoint session;
 - determining if any expected data was not received;
 - if some expected data was not received, sending a data repair request to the sender requesting that the ~~expected-but-not-received~~ expected-but-not-received data be resent; and
 - retransmitting from the sender all of the requested expected-but-not-received data via the point-to-multipoint session.
2. (Currently Amended) The method of claim 1, further comprising:
 - after the sender retransmits the requested expected-but-not-received data, if some data was still not received, scheduling point-to-point repair sessions for specific receivers that expected data that was not received;
 - sending data still not received to the specific receivers via point-to-point sessions according to the point-to-point repair session schedule.
3. (Currently Amended) The method of claim 2, wherein scheduling point-to-point repair sessions further comprises specifying a randomization mechanism to randomize point-to-point data repair over a certain time period after the sender has retransmitted the requested expected-but-not-received ~~not-received~~ data.
4. (Original) The method of claim 2, wherein scheduling point-to-point repair sessions further comprises:
 - If point-to-multipoint repair is possible for a receiver, then
 - uniformly randomizing data repair requests over a time period X starting from the end of the initial transmitting of data from the sender to the receivers via the point-to-multipoint session;

Atty. Dkt. No. 037145-3101

else

waiting until a certain time Y after the initial transmitting of data from the sender to the receivers via the point-to-multipoint session and then randomizing the data repair requests over a time period Z.

5. (Original) The method of claim 2, wherein scheduling point-to-point repair sessions comprises sending a point-to-point repair token from the sender to the plurality of receivers to announce when point-to-point repair will begin.

6. (Original) The method of claim 3, wherein the randomization mechanism is configured to take into account the number of receivers included in the plurality of receivers.

7. (Original) The method of claim 6, further comprising:
determining the number of receivers in the plurality of receivers; and
computing the randomization values for the randomization mechanism based on the determined number of receivers.

8. (Original) The method of claim 7, wherein computing the randomization values further comprises looking up the randomization values up in a look-up table based on the determined number of receivers.

9. (Currently Amended) A point-to-multipoint communication system ~~capable of~~ for repairing data, the system comprising:

a sender device ~~capable of~~ for transmitting data via point-to-multipoint communications;

a plurality of receivers ~~capable of~~ for receiving data from the sender device;

wherein the sender device is configured to transmit data to the plurality of receivers via a point-to-multipoint session;

the plurality of receivers are configured to receive data transmitted by the sender device, determine if any expected data was not received, and, if so, send a data repair request back to the sender device requesting that the ~~expected-but-not-received~~ expected-but-not-received data be resent; and

Atty. Dkt. No. 037145-3101

the sender device is configured to receive data repair requests from the plurality of receivers and to retransmit all of the requested expected-but-not-received data via the point-to-multipoint session.

10. (Currently Amended) The system of claim 9 wherein the sender device is further configured to schedule point-to-point data repair sessions with the plurality of receivers after retransmission of the requested expected-but-not-received data and the sender is configured to send ~~expected-but-not-received~~ expected-but-not-received data to the plurality of receivers via point-to-point sessions.

11. (Original) The system of claim 10 wherein the sender device is further configured to specify a randomization mechanism to delay point-to-point data repair.

12. (Original) The system of claim 11 wherein the sender can determine the number of receivers on the point-to-multipoint session and can compute a randomization mechanism that is based on the determined number of receivers.

13. (Original) The system of claim 10 wherein the sender is configured to send a point-to-point repair token to the plurality of receivers to announce when point-to-point repair will begin.

14. (Original) The system of claim 10 further comprising a look-up table for determining the point-to-point repair schedule.

15. (Currently Amended) A computer code product embodied on a computer readable medium, the computer code product comprising:

computer code configured to:

transmit data from a sender to a plurality of receivers via a point-to-multipoint session;

determine if expected data was not received at any of the plurality of receivers;

make a data repair request if any expected data was not received at any of the plurality of receivers; and

Atty. Dkt. No. 037145-3101

retransmit all of the ~~expected-but-not-received~~ requested expected-but-not-received data to the plurality of receivers via the point-to-multipoint session.

16. (Currently Amended) The computer code product of claim 15, wherein the computer code is further configured to schedule point-to-point data repair sessions after retransmission of the ~~expected-but-not-received~~ requested expected-but-not-received data.

17. (Original) The computer code product of claim 15 wherein the computer code is further configured to determine the number of receivers on the point-to-multipoint session and schedule the point-to-point data repair sessions based on the determined number of receivers.

18. (Currently Amended) A sender device for use in a point-to-multipoint communication system, the sender device comprising:

means for transmitting data to a plurality of receivers via a point-to-multipoint session;

means for receiving data repair requests from the plurality of receivers requesting ~~expected-by-not-received~~ expected-but-not-received data;

means for retransmitting all of the ~~expected-but-not-yet-received~~ requested expected-but-not-received data via a point-to-multipoint session.

19. (Currently Amended) The sender device of claim 18 further comprising means for scheduling point-to-point data repair sessions with the plurality of receivers after retransmitting the ~~expected-but-not-yet-received~~ requested expected-but-not-received data.

20. (Original) The sender device of claim 18 wherein the sender device further comprises means for determining the number of receivers using the point-to-multipoint session wherein the sender is configured to schedule the point-to-point data repair sessions based on the determined number of receivers.

21. (Previously Presented) A method for data repair in a point-to-multipoint communication system, the method comprising:

transmitting data from a sender to a plurality of receivers via a point-to-multipoint session;

Atty. Dkt. No. 037145-3101

received; determining if any of the plurality of receivers expected data that was not
determining the number of receivers using the point-to-multipoint session;
computing randomization values for a randomization mechanism based on the
determined number of receivers;
scheduling point-to-point repair sessions with any of the plurality of receivers
that expected data that was not received; and
delaying the point-to-point data repair sessions based on the computed
randomization values.

22. (Previously Presented) A computer code product embodied on a computer
readable medium, the computer code product comprising:

computer code configured to:

transmit data from a sender to a plurality of receivers via a point-to-
multipoint session;
determine if expected data was not received at any of the plurality of
receivers;
make a data repair request if any data was not received at any of the
plurality of receivers;
determine the number of receivers on the point-to-multipoint session;
schedule point-to-point data repair sessions for each receiver that did
not receive all expected data; and
delaying the point-to-point data repair session based on the number of
determined receivers.

23. (Currently Amended) A sender device for use in a point-to-multipoint
communication system, the sender device comprising:

means for transmitting data to a plurality of receivers via a point-to-multipoint
session;

means for receiving data repair requests from the plurality of receivers
requesting ~~expected but not received~~ expected-but-not-received data;

Atty. Dkt. No. 037145-3101

session; means for determining the number of receivers using the point-to-multipoint

wherein the sender device is configured to schedule point-to-point data repair sessions with receivers that did not receive all expected data; and

delaying the point-to-point data repair session based on the determined number of receivers.

24. (Currently Amended) A point-to-multipoint communication system ~~capable of~~ for repairing data, the system comprising:

a sender device ~~capable of~~ for transmitting data via point-to-multipoint communications;

a plurality of receivers ~~capable of~~ for receiving data from the sender device;

wherein the sender is configured to transmit data to the plurality of receivers via a point-to-multipoint session;

the plurality of receivers being configured to receive data transmitted by the sender device, determine if any expected data was not received, and if so, send a data repair request back to the sender device requesting that the ~~expected but not received~~ expected-but-not-received data be resent;

the sender being configured to determine the number of receivers on the point-to-multipoint session and to determine a randomization mechanism based on the determined number of receivers;

the sender being configured to schedule point-to-point repair sessions with receivers that expected data that was not received, the point-to-point repair sessions being delayed based on the randomization mechanism.